High Velocity Outdoor Rated Air Circulator PFO Series





Model Code: PFO -24 A: Series B: Fan Diameter -24 = 24" -30 = 30"



- Outdoor rated for wet locations
- 80 degree oscillating motion
- Heavy duty air circulation
- Available in 24" & 30" models
- Waterproof totally enclosed motor
- 3-speed switch controls airflow output
- Direct drive motor for dependability
- Wall mounted to direct airflow
- Optional misting kit available
- Scratch resistant, powder-coated finish
- 3 aerodynamically balanced blades
- · Heavy duty steel fan guards
- Meets OSHA 1910.212(A)(5) requirements
- 9 Ft. 120V grounded cord & plug
- 1-year limited warranty

The King High Velocity Commercial Air Circulator

King Commercial High Velocity Outdoor Rated Oscillating Air Circulators are a powerful commercial-grade solution for cooling workshops, warehouses, factories, gyms and more. This oscillating fan motion distributes airflow in a 80 degree sweeping motion or from a fixed position. The waterproof, totally enclosed motor is outdoor rated for wet locations and offers 3-speeds. Featuring 3 aerodynamically balanced aluminum blades for even, steady airflow and to provide maximum air and motor efficiency. The scratch resistant King green finish looks sharp and is easy to clean. Height adjustable from 57" to 75" to direct the air flow where you need it most.

Ordering Information

STOCK CODE	UPC #093319	MODEL NUMBER	DESCRIPTION	CFM	WT. (lbs.)
А	33151	PF0-24	24" Outdoor Rated Oscillating Circulator With Pedestal Base	7435	67.2
А	33152	PF0-30	30" Outdoor Rated Oscillating Circulator With Pedestal Base	7204	73.3
Δ	33153	PFO-MISTKIT	Add-On Accessory For Ontional Misting Feature		

PFO Series



